

MONGOOSE

MONGOOSE DUMP BODY



DESIGNED FOR ROCK, BROKEN CONCRETE, DEMOLITION AND OTHER HIGH-IMPACT JOBS THE OTHERS BACK AWAY FROM

FEATURES OPTIONAL AR-450 FRONT, DOGHOUSE, BODY AND GATE

AVAILABLE IN 3/16, 1/4 & 5/16 THICKNESSWITH OR WITHOUT CROSSMEMBERS







RIGID UNDERBODY

The understructure is manufactured with an 8"x 2" x 1/4" tube main frame, 6"x 4"x 10 gauge channel crossmembers on 12" centers.

Crossmembers are solid welded on each side to the floor and main frame.



MOUNTING SADDLE & HYDRAULIC TANK

Fabricated on site with industry leading quality control standards.









Lufkin Manufacturing 20020 Interstate 30 Benton, AR 72019 Ph: (501) 316-4040 Fax: (501) 634-4141 www.lufkinmfg.com











Authorized Distributor:



UPPER TAILGATE HINGE

Built of 3/4" AR-450 steel hinge arms, 3/8" Hi-Tensile steel side plates, three casehardened bushings and a removable pin designed to grease all three bushings ensuring longer life and easier maintenance.



TAILGATE LATCH **ASSEMBLY**

Constructed with a 5/8" AR-200 steel latch arm, five grease pivot points and operated with a 3.5" doubleacting air cylinder. Remains closed even in case of air malfunction.



REAR HINGE

Standard 1-15/16" Hinge Pin with 1/2" wall greaseable bushings.

Some equipment and features shown are optional. See dealer for additional information on options.